

PC8019

Magic Rust Converter



Solutions you can count on!

DESCRIPTION

Mr McKenic®-Magic Rust Converter is a supreme product that converts rust (new and old) into a protective black polymeric coating that adheres firmly to metal surfaces, preventing further corrosion.

In most cases, end users remove the rust from the metal surface by sand-blasting/grinding. Despite the tediousness of the procedure, rust resurfaces within a short period of time as the surface is still exposed to elements of environment, mainly moisture and oxygen.

Mr McKenic®-Magic Rust Converter offers an effective yet simpler procedure by converting the existing rust into an inert coating that seals up the metal surface from moisture and oxygen. After the conversion, there exists a strong molecular bondage between the converted layer and metal surface, making it very difficult to be removed. As a result, the rust stops spreading and the duration of protection is much extended. It makes a wonderful 'touch-up' tool where re-painting may not be required. However, for aesthetic purposes, surface can be painted over.

APPLICATIONS

Mr McKenic®-Magic Rust Converter can be used on any metal surface being corroded. It is widely used in maintenance workshops, oil rigs, military vehicles, oil rigs, onboard vessels, shipyards, metal tanks and pipings in refineries etc.

DIRECTIONS

1. Remove all loose rust with a wire-brush. Scrap off to a thin layer before application if the rust is too thick
2. Ensure that surface is cleaned and oil-free before application
3. *Shake Bottle well before use.*
4. Using a brush or roller, apply a generous layer of *Mr McKenic®-Magic Rust Converter* onto the rusty surface.
5. Leave it for at least 8 hours to cure thoroughly. To accelerate curing process, apply & leave it under the sun.
6. For maximum protection, apply 2 layers of coats.
7. If re-painting is required, apply 1 coat and paint over.
8. For much enhanced protection, apply *Mr McKenic®-Zinc Galvanising Compound*.

Note:

There may be separation of contents due to storage conditions. Stir well before use. The product is still effective. Keep in cool area (~20°C) for storage.

HANDLING PRECAUTIONS

1. For professional use only. To be used in well ventilated environment.
2. In case of contact with eyes, rinse thoroughly with water and seek medical advice immediately.
3. If swallowed, take plenty of water and seek medical advice immediately.
4. Avoid prolonged contact with skin.
5. Put on gloves for sensitive skin.
6. Keep out of reach of children.
7. Additional information may be obtained from Material Safety Data Sheet (MSDS).

PRODUCT PROPERTIES

Physical State	Liquid	
Colour	White Milky	
Solubility (In Water)	Soluble	
Density	N.A.	
Packing	PC8019-P170	170ml Btl
	PC8019-P1	1Ltr Btl
	PC8019-P5	5Ltr Btl

BENEFITS

- Convert Rust to a Tough Black Coating to Give Better Wear and Tear Protection
- Provides Long Term Indoor or Outdoor Protection
- Easy Application
- Ready to Use
- Saves Time and Labour
- Non-Flammable



Product Data reflects results of laboratory tests and is intended to indicate general characteristics only. Because Vance Chemicals Pte Ltd cannot anticipate or control the many different conditions under which this information and/or product may be used, it does not guarantee the applicability or the accuracy of this information or the suitability of its products in any given situation. Users of Vance Chemicals Pte Ltd products should conduct their own tests to determine the suitability of each product for their particular purposes. © 2009 Vance Chemicals Pte Ltd. All rights reserved.

Vance Chemicals Pte Ltd

No 24 Gul Lane Singapore 629418
Tel: (65) 6863 0863 Fax: (65) 6862 0862
Email: sales@mr-mckenic.com
Website: <http://www.mr-mckenic.com>
RCB No: 200918824E



VCPL-CAT-PC8019-R1
Revision Date: 1 DECEMBER 2009